

**B.PRO**  
CATERING SOLUTIONS



# SHELF TROLLEYS

**A major fleet for safe food transport**



← Smooth surfaces for easy cleaning and maximum hygiene

← Push-through protection on both sides

← Maximum stability thanks to welded cross struts on both sides

# HAVE A GOOD TRIP

**Shelf trolleys from B.PRO Catering Solutions. Quality comes first.**

B.PRO shelf trolleys impress thanks to their ideal combination between stability and mobility since food also needs to be safely transported from A to B.

The high-grade craftsmanship is particularly evident in the details: the tube clamps features a smooth surface, meaning no tapering, no dirty edges, greater hygiene and more design.

Loading, storing, transporting and serving. B.PRO shelf trolleys are ideal for multifunctional use and provide plenty of room for GN containers, GN sheets, GN trays and GN grates.

Select from 19 models and a useful accessories range with stainless steel and Resopal panelling, and dust protection and insulating hoods.

Look forward to using a strong trolley fleet that provides the right model for every occasion.

**B.PRO shelf trolleys:  
long operating life featured as  
standard.**



#### **All-round stability**

The robust, all-round base frame adds extra stability while also protecting the support rail against deformation.



#### **Safety first**

The special U-profile of the support rails acts as an integrated tip safety device.



#### **Connected crosswise**

Cross struts increase the overall stability. Thanks to their offset arrangement, they can also be used as support rails.



#### **Smooth surface**

Tube clamps without tapering. This not only guarantees a beautiful, functional design but also maximum hygiene since there are no edges collecting dirt.



#### **Also safe during transport**

The push-through protection is mounted on both sides and thus ensures safe transport in every direction.



#### **Bumper rail fitted as standard**

All shelf trolleys are equipped with a strong bumper rail. They protect the trolley and inventory against damage.

## B.PRO SHELF TROLLEYS



| Model                       | RWRA 850<br>Shelf trolley                                      | RWRA 851<br>Shelf trolley          | RWRA 852<br>Shelf trolley          | RWR 751<br>Shelf trolley           |
|-----------------------------|--|------------------------------------|------------------------------------|------------------------------------|
| Special features            | with worktop   |                                    | 2-piece with worktop               |                                    |
| Dimensions (L x W x H)      | 460 x 613 x 845 mm   | 662 x 733 x 845 mm                 | 820 x 613 x 845 mm                 | 662 x 733 x 845 mm                 |
| Support pairs               | 8 pair   |                                    | 16 pair                            | 7 pair                             |
| Support spacing             | 73 mm  |                                    |                                    |                                    |
| Capacity                    | 8 GN 1/1 or 16 GN 1/2  | 8 GN 2/1 or 16 GN 1/1              | 16 GN 1/1 or 32 GN 1/2             | 7 GN 2/1 or 14 GN 1/1              |
| Weight (synthetic castors)  | 15 kg  | 20 kg                              | 22 kg                              | 16 kg                              |
| Load-bearing capacity       | 100 kg   | 200 kg                             | 180 kg                             | 200 kg                             |
| Castor model                | 125 mm in diameter, 4 steering castors, 2 of which have brakes |                                    |                                    |                                    |
| Castor version<br>Order no. | Synthetic*<br><b>572 926</b>                                   | Synthetic*<br><b>572 928</b>       | Synthetic*<br><b>572 930</b>       | Synthetic*<br><b>572 932</b>       |
| Castor version<br>Order no. | Galvanised steel<br><b>572 925</b>                             | Galvanised steel<br><b>572 927</b> | Galvanised steel<br><b>572 929</b> | Galvanised steel<br><b>572 931</b> |

\* Corrosion-resistant in compliance with DIN 18867-8





| Model                       | RWR 160<br>Shelf trolley                                       | RWR 160-20<br>Shelf trolley        | RWR 161<br>Shelf trolley           | RWR 161-20<br>Shelf trolley        |
|-----------------------------|--|------------------------------------|------------------------------------|------------------------------------|
| Dimensions (L x W x H)      | 460 x 613 x 1645 mm  | 460 x 613 x 1800 mm                | 662 x 733 x 1645 mm                | 662 x 733 x 1800 mm                |
| Support pairs               | 18 pair  | 20 pair                            | 18 pair                            | 20 pair                            |
| Support spacing             | 73 mm  | 75 mm                              | 73 mm                              | 75 mm                              |
| Capacity                    | 18 GN 1/1 or 36 GN 1/2   | 20 GN 1/1 or 40 GN 1/2             | 18 GN 2/1 or 36 GN 1/1             | 20 GN 2/1 or 40 GN 1/1             |
| Weight (synthetic castors)  | 15 kg  | 19 kg                              | 25 kg                              |                                    |
| Load-bearing capacity       | 200 kg   |                                    |                                    |                                    |
| Castor model                | 125 mm in diameter, 4 steering castors, 2 of which have brakes |                                    |                                    |                                    |
| Castor version<br>Order no. | Synthetic*<br><b>572 934</b>                                   | Synthetic*<br><b>572 303</b>       | Synthetic*<br><b>572 936</b>       | Synthetic*<br><b>572 304</b>       |
| Castor version<br>Order no. | Galvanised steel<br><b>572 933</b>                             | Galvanised steel<br><b>568 497</b> | Galvanised steel<br><b>572 935</b> | Galvanised steel<br><b>568 498</b> |

\* Corrosion-resistant in compliance with DIN 18867-8

## B.PRO SHELF TROLLEYS



| Model                       | RWRR 161<br>Shelf trolley                                      | RWRE 161<br>Shelf trolley          | RWR-VP 163<br>Shelf trolley                                   | RWR SK-161<br>Shelf trolley                          |
|-----------------------------|--|------------------------------------|---|--|
| Special features            | when empty, can be pushed into each other to save space        | for roll-in refrigerators          | for storing and providing pre-portioned and lidded cold items | Salad and dessert serving trolley with serving doors |
| Dimensions (L x W x H)      | 662 x 734 x 1645 mm  | 587 x 658 x 1645 mm                | 671 x 832 x 1675 mm   | 662 x 733 x 1645 mm                                  |
| Support pairs               | 18 pair  |                                    | 12 pair   | 5 pair + 9 pair                                      |
| Support spacing             | 73 mm  |                                    | 115 mm  | 115 mm + 73 mm                                       |
| Capacity                    | 18 GN 2/1 or<br>36 GN 1/1                                      | 18 GN 2/1 or<br>36 GN 1/1          | 24 EN trays   | 14 GN 2/1-20 or<br>14 BZG 2/1-20                     |
| Weight (synthetic castors)  | 25 kg  |                                    | 18 kg   | 30 kg  |
| Load-bearing capacity       | 200 kg   |                                    | 240 kg  | 200 kg   |
| Castor model                | 125 mm in diameter, 4 steering castors, 2 of which have brakes |                                    |   |  |
| Castor version<br>Order no. | Synthetic*<br><b>572 938</b>                                   | Synthetic*<br><b>572 940</b>       | Synthetic*<br><b>572 923</b>                                  | Synthetic*<br><b>572 944</b>                         |
| Castor version<br>Order no. | Galvanised steel<br><b>572 937</b>                             | Galvanised steel<br><b>572 939</b> | Galvanised steel<br><b>572 945</b>                            | Galvanised steel<br><b>572 943</b>                   |

\* Corrosion-resistant in compliance with DIN 18867-8

We will be happy to provide you with additional information on these products and the entire B.PRO product line on request (see back for address).

## B.PRO SHELF TROLLEYS FOR USE WITH COOK & CHILL



| Model                       | RWR 2<br>Shelf trolley   | RWR 3<br>Shelf trolley                | RWR 2-A<br>Shelf trolley                          | RWR 3-A<br>Shelf trolley                          |
|-----------------------------|--|---------------------------------------|---|---|
| Special features            | 2-piece,<br>for hanging GN containers                          | 3-piece,<br>for hanging GN containers | 2-piece, with mount,<br>for hanging GN containers | 3-piece, with mount,<br>for hanging GN containers |
| Dimensions (L x W x H)      | 812 x 625 x 900 mm   | 1165 x 625 x 900 mm                   | 812 x 625 x 1200 mm                               | 1165 x 625 x 1200 mm                              |
| Support pairs               | 6 pair + 2 pair  | 9 pair + 3 pair                       | 6 pair + 2 pair<br>+ 2 pair in mount              | 9 pair + 3 pair<br>+ 3 pair in mount              |
| Support spacing             | 165 mm   |                                       |   |   |
| Capacity                    | 8 GN 1/1   | 12 GN 1/1                             | 10 GN 1/1   | 15 GN 1/1   |
| Weight (synthetic castors)  | 17 kg  | 23 kg                                 | 22 kg   | 31 kg   |
| Load-bearing capacity       | 60 kg  | 70 kg                                 |   | 80 kg   |
| Castor model                | 125 mm in diameter, 4 steering castors, 2 of which have brakes |                                       |   |   |
| Castor version<br>Order no. | Synthetic*<br><b>572 305</b>                                   | Synthetic*<br><b>572 306</b>          | Synthetic*<br><b>572 307</b>                      | Synthetic*<br><b>572 308</b>                      |
| Castor version<br>Order no. | Galvanised steel<br><b>568 432</b>                             | Galvanised steel<br><b>568 446</b>    | Galvanised steel<br><b>568 403</b>                | Galvanised steel<br><b>568 416</b>                |

\* Corrosion-resistant in compliance with DIN 18867-8

## B.PRO SHELF TROLLEYS FOR USE WITH EUTECTIC PLATES



| Model                       | RWR-EP 23<br>Shelf trolley  | RWR-EP 46<br>Shelf trolley               |
|-----------------------------|---|--|
| Special features            | for transporting and storing eutectic plates in cold storage houses |  |
| Dimensions (L x W x H)      | 464 x 619 1675 mm   | 668 x 739 x 1675 mm                      |
| Support pairs               | 23 pair   |  |
| Support spacing             | 58 mm   |  |
| Capacity                    | 23 eutectic plates (lengthwise insertion)                           | 46 eutectic plates (crosswise insertion) |
| Weight (synthetic castors)  | 31 kg   | 39 kg                                    |
| Load-bearing capacity       | 200 kg  |  |
| Castor model                | 125 mm in diameter, 4 steering castors, 2 of which have brakes      |  |
| Castor version<br>Order no. | Synthetic*<br><b>573 962</b>  | Synthetic*<br><b>573 963</b>             |

\* Corrosion-resistant in compliance with DIN 18867-8



## B.PRO SHELF TROLLEYS FOR EURO CONTAINERS OR BAKING TRAYS



ainers

| Model                                  | RWR-E 6 x 4<br>Shelf trolley to transport Euro containers      | RWR-B 6 x 4<br>Shelf trolley to transport baking trays |
|--|--|--|
| Special features                       | For 600 x 400 mm Euro containers                               | For 600 x 400 mm baking trays                          |
| Dimensions (L x W x H)                 | 686 x 536 x 1515 mm  | 686 x 536 x 1729 mm                                    |
| Support pairs                          | 5 pairs  | 20 pairs   |
| Support spacing                        | 245 mm   | 73 mm  |
| Capacity                               | 5 E2 Euro containers 600 x 400 x 200 mm                        | 20 baking trays 600 x 400 mm                           |
| Weight (synthetic castors)             | 14 kg  | 21.5 kg  |
| Load-bearing capacity per support pair | 25 kg  | 25 kg  |
| Overall load-bearing capacity          | 125 kg   | 200 kg   |
| Castor model                           | 125 mm in diameter, 4 steering castors, 2 of which have brakes |  |
| Castor version<br>Order no.            | Synthetic*<br><b>575 102</b>                                   | Synthetic*<br><b>575 104</b>                           |
| Castor version<br>Order no.            | Galvanised steel<br><b>575 103</b>                             | Galvanised steel<br><b>575 105</b>                     |

\* Corrosion-resistant in compliance with DIN 18867-8

## TRANSPORT TROLLEYS FOR EURO CONTAINERS



| Model                         | TRE 6 x 4<br>Platform trolley for Euro containers              | TRE 6 x 4<br>Platform trolley for Euro containers              | TWE 6 x 4<br>Transport trolley for Euro containers                  |
|-------------------------------|--|--|---|
| Special features              | With push handle   | Without push handle  |   |
| Dimensions (L x W x H)        | 742 x 430 x 950 mm   | 640 x 430 x 201 mm   | 940 x 700 x 1585 mm   |
| Platform height               | 201 mm   | 201 mm   |   |
| Platform size                 | 640 x 430 mm   | 640 x 430 mm   | Capacity: 12 E2 boxes   |
| Weight                        | 10 kg  | 8 kg   | 50 kg   |
| Overall load-bearing capacity | 120 kg   | 120 kg   | 350 kg (175 kg per shelf)   |
| Castor model                  | 125 mm in diameter, 4 steering castors, 2 of which have brakes | 125 mm in diameter, 4 steering castors, 2 of which have brakes | 160 mm in diameter, 2 fixed castors, 2 steering castors with brakes |
| Castor version<br>Order no.   | Synthetic*<br><b>575 098</b>                                   | Synthetic*<br><b>575 096</b>                                   | -   |
| Castor version<br>Order no.   | Galvanised steel<br><b>575 099</b>                             | Galvanised steel<br><b>575 097</b>                             | Galvanised steel<br><b>575 101</b>                                  |

\* Corrosion-resistant in compliance with DIN 18867-8

### Details

### Optional for TWE 6 x 4



TWE 6 x 4 with ergonomic push handle



TWE 6 x 4 with optional push-through protection on both sides

## ACCESSORIES

| Illustration  | Model   | Designation   | For models   | Order no.                           |
|---|---|---|--|-------------------------------------|
|    | <b>Dust protection hood for shelf trolley</b> | <b>Dust protection hood</b> consisting of transparent, tear-proof polyethylene, 200 µ, 5-sided protection, with Velcro fastener   | RWR 160  | <b>573 771</b>                      |
|   |   |   | RWR 161  | <b>568 772</b>                      |
|   |   |   | RWRR 161   | <b>568 757</b>                      |
|   |   |   | RWRR 162   | <b>573 018</b>                      |
|   |   |   | RWR-VP 163   | <b>568 773</b>                      |
|    | <b>Insulating hood for shelf trolley</b>      | <b>Insulating hood</b> , interior and exterior sides made of food-safe, tear-resistant polyethylene, 300 µ, filling: polypropylene 3 mm thick, aluminised on both sides, 5-sided protection, with Velcro fastener (not suitable for RWR with panelling) | RWR 160  | <b>568 774</b>                      |
|   |   |   | RWR 161  | <b>568 775</b>                      |
|   |   |   | RWRR 161   | <b>568 905</b>                      |
|   |   |   | RWRR 162   | <b>568 776</b>                      |
| RWR-VP 163  | <b>573 017</b>                                |   |  |                                     |
|   | <b>Panelling made of stainless steel</b>      | <b>Panelling</b> , 2- or 3-sided made of stainless steel  | for all RWR models   | <b>Please specify when ordering</b> |
|  | <b>Resopal panelling</b>                      | <b>Panelling</b> , 2- or 3-sided made of Resopal  | all RWR,<br><br>not available for:<br>RWRR 161<br>RWRE 161<br>RWR SK 161   |                                     |
|  | <b>Top surface</b>                            | <b>Trolley top</b> made of stainless steel  | RWR 160<br>RWR 161<br>RWR 162  |                                     |
|  | <b>Push handle</b>                            | <b>Push handle</b> made of stainless steel  | RWR 2, RWR 3,<br>RWR 2-A, RWR 3-A,<br>RWR 160, RWR 160-20,<br>RWR 161, RWR 161-20,<br>RWR 162                    |                                     |
|  | <b>Transport safety catch</b>                 | <b>Transport locking bar</b> made of stainless steel  | RWR 160, RWR 161, RWR 162,<br>RWR-VP 163,<br>RWR 160-20, RWR 161-20,<br>RWRA 850, RWRA 851, RWRA 852,<br>RWR 751 |                                     |

## THE B.PRO GROUP

Our customers are as diverse and varied as our portfolio. To ensure we do our very best for every client, we concentrate our skills, abilities and capacities in two highly specialised business units: B.PRO Catering Solutions – Products and systems for professional commercial kitchens. ENOXX Engineering – Custom-made high-precision pieces using stainless steel, aluminium or synthetics for industry.

All business units of B.PRO hold DIN EN ISO9001:2015 certification, guaranteeing a high standard of reliability and customer orientation.

B.PRO GmbH  
B.PRO Catering Solutions  
P.O. Box 13 10  
75033 Oberderdingen  
Germany  
Phone +49 7045 44-81900  
[catering.export@bpro-solutions.com](mailto:catering.export@bpro-solutions.com)  
[www.bpro-solutions.com](http://www.bpro-solutions.com)

**B.PRO**  
CATERING SOLUTIONS